

JEEP WRANGLER JL 2018 ON

FRONT <i>Estimated Lift:</i> SPORT 3.5" (90mm) RUBICON 2.5" (65mm)	SWB PETROL ENGINE			LWB PETROL ENGINE		
	PART NUMBER	QTY	UNIT PRICE \$	PART NUMBER	QTY	UNIT PRICE \$
SPRING: NO BAR	3133 1	1		3134 1	1	
NITROCHARGER SPORT	60150 3	2		60150 3	2	
SPRING: BAR AND WINCH	3134 1	1		3135 1	1	
NITROCHARGER SPORT	60150 3	2		60150 3	2	
FRONT LOWER CONTROL ARM - ADJUSTABLE	LCAJLFR 2	1		LCAJLFR 2	1	
BUMP STOP KIT	FK92 3			FK92 3		
SWAY BAR LINK KIT	FK93 3			FK93 3		
TRIM PACKER	OMEJKPF10 1			OMEJKPF10 1		

REAR <i>Estimated Lift:</i> SPORT 3.5" (90mm) RUBICON 2.5" (65mm)	SWB MODELS			LWB MODELS		
	PART NUMBER	QTY	UNIT PRICE \$	PART NUMBER	QTY	UNIT PRICE \$
SPRING: MEDIUM LOAD	3136 1	1		3137 1	1	
NITROCHARGER SPORT	60151 3	2		60151 3	2	
SPRING: CONSTANT 150 KGS	3137 1	1		3138 1	1	
NITROCHARGER SPORT	60151 3	2		60151 3	2	
SPRING: CONSTANT 300 KGS	N/A			3139 1	1	
NITROCHARGER SPORT	60151 3	2		60151 3	2	
TRIM PACKER	OMEJKPR10 1			OMEJLPR10 1		

REMARKS:

- 1 For trim adjustment use - Front: OMEJKPF10 Rear: OMEJLPR10. Do not fit more than one (1) packer per coil spring.
- 2 Fitment of LCAJLFR Front Lower Control Arm is **required** to restore wheel alignment castor settings.
- 3 Fitment of FK92 is **mandatory**. FK92 Bump Stop Kit prevents shock absorbers from going solid and fitment of larger tyres. Fitment of FK93 is **mandatory**. FK93 allows the shocks to extend freely without limit or contact.

Lift increase is approximate and will depend on vehicles weights.

When fitting larger than original diameter tyres, it is a requirement to fit aftermarket wheels (rims) that have a greater offset (less backspacing) to ensure that sufficient clearance is given between the tyre to sway bar, sway bar links and control arms.